

Pipe ND	Pipe OD	Coupling range	Working pressure (bar)	L	Kg
DN15	20.0	19.5 ~ 20.5	16	60	0,23
	21.7	21.0 ~ 22.0	16	60	0,23
DN20	25.0	24.0 ~ 26.0	16	60	0,25
	27.2	26.0 ~ 28.0	16	60	0,25
DN25	28.2	26.4 ~ 29.0	16	60	0,25
	30.0	29.0 ~ 31.0	16	60	0,27
	32.0	31.0 ~ 33.0	16	60	0,27
DN32	34.0	33.0 ~ 35.0	16	60	0,27
	38.0	37.0 ~ 39.0	16	60	0,29
	40.0	39.5 ~ 41.3	16	60	0,29
DN40	42.7	42.0 ~ 44.0	16	60	0,29
	44.5	44.0 ~ 46.0	16	60	0,29
	48.6	47.5 ~ 49.5	16	60	0,31
DN50	50.8	49.2 ~ 51.5	16	60	0,31
	54.0	53.0 ~ 55.0	16	80	0,68
DN65	57.0	56.0 ~ 58.0	16	80	0,68
	60.5	59.0 ~ 61.5	16	80	0,68
	63.0	62.0 ~ 64.0	16	80	0,68
	66.7	65.4 ~ 68.3	14	80	0,74
DN80	69.0	68.5 ~ 71.0	14	80	0,74
	73.0	72.5 ~ 75.5	14	80	0,74
	76.3	75.0 ~ 78.0	14	80	0,74
DN100	79.9	78.8 ~ 82.0	14	110	1,55
	84.0	82.5 ~ 85.5	14	110	1,55
	89.1	88.0 ~ 91.0	14	110	1,55
DN125	101.6	100.0 ~ 103.0	14	110	1,55
	104.0	102.0 ~ 105.0	14	110	1,73
	106.3	105.0 ~ 107.5	14	110	1,73
	108.0	106.0 ~ 109.0	14	110	1,73
DN150	114.3	113.0 ~ 116.0	14	110	1,73
	127.0	125.0 ~ 129.0	14	111	2,22
	129.0	127.5 ~ 130.0	14	111	2,22
	133.0	131.0 ~ 135.0	14	111	2,22
DN175	139.8	138.0 ~ 142.0	14	111	2,22
	141.3	139.5 ~ 143.5	14	111	2,22
	154.0	151.5 ~ 155.5	12	111	2,41
	159.0	156.0 ~ 160.0	12	111	2,41
DN200	165.2	164.0 ~ 167.0	12	111	2,41
	168.3	166.0 ~ 170.0	12	111	2,41
	180.0	178.0 ~ 182.0	10	111	2,41
	200.0	198.0 ~ 203.0	8	150	5,18
DN250	204.0	202.0 ~ 206.0	8	150	5,18
	216.3	214.0 ~ 218.5	8	150	5,18
	219.1	216.5 ~ 221.5	8	150	5,18
	254.0	251.0 ~ 257.0	8	150	5,83
DN300	267.4	262.0 ~ 269.0	8	150	5,83
	273.1	270.0 ~ 276.0	8	150	5,83
	304.0	301.5 ~ 308.0	7	150	6,55
DN350	318.5	316.0 ~ 322.5	7	150	6,55
	323.9	322.0 ~ 328.0	7	150	6,55
	355.6	352.0 ~ 360.0	7	150	7,20
DN400	406.4	402.0 ~ 410.0	6	150	7,70
DN450	457.2	453.0 ~ 460.0	6	150	8,40
DN500	508.0	504.0 ~ 512.0	5	150	9,10
DN550	558.8	555.0 ~ 563.0	4.6	150	9,80
DN600	609.6	605.0 ~ 614.0	4.2	150	10,1

No	Part	Material	Code
1	Grip Ring	Stainless Steel	SS 304
2	Seal	NBR (810) EPDM (811)	

