

Pipe ND	Pipe OD	Coupling range	Working pressure (bar)	L	Kg	
DN15	20.0	19.5 ~ 20.5	16	60	0,32	
	21.7	21.2 ~ 22.2	16	60	0,32	
DN20	25.0	24.5 ~ 25.5	16	60	0,32	
	27.2	26.7 ~ 27.7	16	60	0,32	
	28.2	27.5 ~ 29.0	16	60	0,32	
DN25	30.0	29.5 ~ 30.5	16	60	0,34	
	32.0	31.5 ~ 32.5	16	60	0,34	
	34.0	33.0 ~ 34.6	16	60	0,34	
DN32	38.0	37.5 ~ 38.5	16	60	0,36	
	40.0	39.5 ~ 41.5	16	60	0,36	
	42.7	41.9 ~ 43.0	16	60	0,36	
	44.5	44.0 ~ 45.0	16	60	0,36	
DN40	48.6	47.8 ~ 49.0	16	60	0,38	
	50.8	49.5 ~ 51.5	16	60	0,38	
DN50	54.0	53.4 ~ 54.6	16	80	0,60	
	57.0	56.4 ~ 57.6	16	80	0,60	
	60.5	59.0 ~ 61.5	16	80	0,60	
	63.0	62.4 ~ 63.6	16	80	0,60	
DN65	66.7	65.2 ~ 67.3	14	80	0,68	
	69.0	68.0 ~ 70.1	14	80	0,68	
	73.0	71.5 ~ 74.1	14	80	0,68	
	76.3	75.0 ~ 77.2	14	80	0,68	
	DN80	79.9	78.8 ~ 80.8	14	110	1,38
DN80	84.0	83.0 ~ 84.9	14	110	1,38	
	89.1	87.8 ~ 91.0	14	110	1,38	
	101.6	100.4 ~ 102.6	14	110	1,38	
DN100	104.0	103.0 ~ 104.8	14	110	1,60	
	106.3	105.0 ~ 107.4	14	110	1,60	
	108.0	106.5 ~ 108.5	14	110	1,60	
	114.3	113.2 ~ 115.4	14	110	1,60	
DN125	127.0	125.6 ~ 128.4	14	111	2,07	
	129.0	127.5 ~ 130.0	14	111	2,07	
	133.0	131.6 ~ 134.4	14	111	2,07	
	139.8	137.7 ~ 140.9	14	111	2,07	
	141.3	139.7 ~ 142.5	14	111	2,07	
	DN150	154.0	151.5 ~ 155.0	12	111	2,25
DN150	159.0	156.5 ~ 160.0	12	111	2,25	
	165.2	163.3 ~ 166.7	12	111	2,25	
	168.3	166.6 ~ 170.0	12	111	2,25	
	DN175	180.0	178.0 ~ 182.0	10	111	2,25
	DN200	200.0	198.2 ~ 201.5	8	150	4,73
204.0		202.7 ~ 206.7	8	150	4,73	
216.3		214.5 ~ 218.3	8	150	4,73	
219.1		217.0 ~ 221.0	8	150	4,73	
DN250		254.0	251.4 ~ 256.6	8	150	5,40
	267.4	264.8 ~ 270.0	8	150	5,40	
	273.1	270.4 ~ 275.6	8	150	5,40	
DN300	304.0	301.5 ~ 306.6	7	150	6,16	
	318.5	316.0 ~ 322.0	7	150	6,16	
	323.9	321.0 ~ 327.4	7	150	6,16	
DN350	355.6	352.0 ~ 360.0	7	150	7,20	
	DN400	406.4	402.0 ~ 410.0	6	150	7,70

No	Part	Material	Code
1	Grip Ring	Stainless Steel	SS 304
2	Seal	NBR (800) EPDM (801)	

