

GENERAL TERMS

- 000 Standard execution
- 099 Standard execution, undrilled flanges
- 097 Standard execution, flanges drilled ANSI-150
- 098 Standard execution, flanges drilled ANSI-300
- 020 EPDM
- 040 NBR
- 060 Viton

SAFETY VALVES

- 001-099 = Preset pressure in bar
- 619 PTFE seat adjustable 2-12 bar
- 620 PTFE seat adjustable 12-20 bar

STRAINERS

- 001-010 = Mesh size in mm
- 380 Face to face in mm
- 476 Face to face in mm
- 610 Face to face in mm
- 690 Face to face in mm
- 700 Face to face in mm
- 800 Face to face in mm

STOP VALVES / SDNR

- 001 Bellow seated with B.W ends
- 096 undrilled SS trim Regulating disc
- 100 SDNR
- 101 SDNR free disc
- 103 Bellow sealed SDNR
- 104 Bellow sealed
- 105 Bellow sealed regulating disc
- 106 SS-trim Regulating disc
- 107 Conical Rg seat
- 108 PTFE seat
- 109 SS-trim
- 110 SS-trim SDNR
- 111 Rg trim Regulating disc
- 112 Rg trim
- 113 Rg trim SDNR
- 114 Butt weld ends
- 117 Conical Rg seat SDNR
- 118 PTFE seat SDNR
- 120 Rg trim DNV rated
- 121 Rg trim SDNR DNV rated
- 122 SS trim DNV rated
- 123 SS trim SDNR DNV rated
- 124 Lloyds rated
- 125 Lloyds rated SDNR
- 126 Rg seat SS stem DNV rated
- 128 ABS rated
- 130 With indicator
- 131 SDNR with indicator
- 140 Stem in mtrl. 1,4305
- 141 Stem in mtrl. 1,4305 SDNR
- 142 Stem/disc in mtrl. CuSn8
- 197 drilled ANSI-150 SDNR trim
- 198 drilled ANSI-300 SDNR trim
- 199 undrilled SDNR
- 501 with Gearbox
- 599 undrilled with Gearbox

GATE VALVES

- 001 SS stem Rg seat
- 002 SS trim
- 003 ALB stem
- 008 PTFE gland packing
- 011 Non rising stem, SS-stem Rg-seat
- 020 Soft seat EPDM
- 040 Soft seat NBR
- 112 Rg trim
- 114 Butt weld end
- 120 Rg trim DNV rated
- 126 SS stem Rg seat DNV rated
- 132 With indicator and locking device
- 160 PN 160
- 224 Lloyds rated drilled PN 16
- 300 Soft seat NBR
- 301 SS-wedge soft seat NBR
- 420 Direct mounting DNV rated
- 501 With gearbox

BALL VALVES

- 007 25% carbon filled seats
- 077 Alu-bronze trim
- 078 Alu-bronze trim, NPT thread
- 104 L-bore BSP thread DMP
- 105 T-bore BSP thread DMP
- 106 L-bore B.W end DMP
- 107 T-bore B.W end DMP
- 109 SS-trim
- 132 Brass-stem SS-ball
- 133 Butterfly handle
- 275 min. 2,75% Mo
- 292 PFA-lined drilled PN16
- 400 L-bore DMP
- 401 T-bore DMP
- 402 X-bore DM
- 403 Direct mounting pad/ SS trim
- 404 Direct mounting pad/ Brass trim
- 407 Direct mounting pad/ ALB trim
- 408 Direct mounting pad/ Titan trim
- 413 Fire safe approved DMP
- 423 Direct mounting pad SS316L
- 501 With gearbox
- 700 L-port
- 701 T-port
- 888 Blücher end
- BRA Brass-trim
- DMP Direct Mounting Pad

BUTTERFLY VALVES

- 099 undrilled
- 111 Metal seat
- 120 DNV rated
- 501 With gearbox

DIAPHRAGM VALVES

- 010 Natural rubber
- 020 EPDM
- 030 Butyl rubber
- 040 NBR rubber
- 050 Neoprene
- 060 Viton

CHECK VALVES

- 001 Tilting disc with gearbox
- 020 EPDM seat
- 040 NBR seat
- 050 PTFE seat
- 045 45 degree perf.
- 060 60 degree perf.
- 070 70 degree perf.
- 079 SS-disc Viton seat
- 103 Soft seat NBR
- 109 SS-seat
- 112 Rg-seat
- 113 Rg-seat
- 121 DNV rated
- 125 Lloyds rated
- 200 With spring
- 201 Floating ball
- 202 PTFE seat
- 204 Long type
- 250 PTFE seat with spring
- 299 Spigot flange end
- 312 Rg seat with counterw.

VARIOUS

- 001 Steam trap NPT-thread
- 200 Reducing valve
- 411 Reducing valve
- 412 Reducing valve
- 413 Reducing valve
- 414 Reducing valve
- 114 Butt weld end
- 155 With Storz-C Coupling and cap
- 156 With Storz-B Coupling
- 158 NH/NST-thread w. US pin lug blind cap

DIV

- NPT Tapered thread screwed
- NPS Straight thread screwed
- ACT Actuators
- HYD Hydraulic Actuator
- 888 Blücher butt weld