

## PNEUMATIC ACTUATOR QUARTER TURN SINGLE ACTING, ALUMINIUM

### Description

Quarter turn pneumatic actuator of compact design, allowing high torque/size performance. Top mounted indicator and Numur interface. Adjustment range +/- 5° at 0 and 90°. Air supply pressure minimum 2 bar, maximum 8 bar. Operating media dry or lubricated air. Designed to match IP 65. Mounting flange according to ISO 5211. With position indicator.

### Standard & Design

|                    |           |
|--------------------|-----------|
| Material Body      | Aluminium |
| Min temp Op / peak | -20°C     |
| Max temp Op / peak | +80°C     |

### Parts list

| No | Part | Material  | Code      | Comment |
|----|------|-----------|-----------|---------|
|    | Body | Aluminium | Aluminium |         |

### ITEMS

| Item No. |
|----------|
| M40733   |
| M40732   |
| M40734   |
| M40724   |
| M40723   |
| M40728   |
| M40729   |
| M40725   |
| M40730   |
| M40727   |
| M40731   |
| M40726   |
| M40722   |

### Variants

Meson Group's product offering is larger than displayed here. We have the capability to tailor-make products according to customer needs. Please access a resembling product through [www.mesongroup.com](http://www.mesongroup.com) and click "Add with note", to request a customized product.

Measures are in mm. Weights are approximate. The information provided may contain errors or omissions, and no rights may be derived from its content. Meson Group reserves the right to update information at any time without prior notice. For the latest revision, always consult [www.mesongroup.com](http://www.mesongroup.com). Document created 2026-08-14

