


GLOBE VALVE SDNR STRAIGHT, WITH SPRING, GGG40.3/RG5

Description

Straight type, Nodular Cast Iron body, metal seated globe valve with rising stem and bolted bonnet. Raised face flanges.

Standard & Design

Material Body	Ductile Iron
Material Sealing Parts	Copper Alloy
Execution	With Spring
Actuation	Handwheel
Standard	DIN
Connection standard	EN 1092
Face to face standard	EN 558, series 1
Model number	467002;467001



Parts list

No	Part	Material	Code	Comment
1	Body	Nodular Cast Iron	GGG40	
2	Bonnet	Nodular Cast Iron	GGG40	
3	Seat	Bronze	RG5	
4	Disc	Bronze	RG5	
5	Stem	Special Brass	Som59	
6	Gland packing	Graphite		
7	Gasket	Graphite		
8	Handwheel	Cast Iron	GG25	
9	Spring	Stainless Steel	1.4301	

Measures are in mm. Weights are approximate. The information provided may contain errors or omissions, and no rights may be derived from its content. Meson Group reserves the right to update information at any time without prior notice. For the latest revision, always consult www.mesongroup.com. Document created 2026-08-13



ITEMS

PN16

Item No.	Connection	DN	nxød	Hcd	L	H	ØM	Kg
150-00002055	PN16	15	4x14	65				
150-00002056	PN16	20	4x14	75				
150-00002057	PN16	25	4x14	85	160	198	120	5.4
150-00002058	PN16	32	4x18	100				
150-00002059	PN16	40	4x18	110	200	221	140	9.8
150-00002060	PN16	50	4x18	125	230	224	140	13
150-00002061	PN16	65	4x18	145				
150-00002062	PN16	80	8x18	160	310	292	160	25
150-00002063	PN16	100	8x18	180	350	325	160	35
150-00002064	PN16	125	8x18	210				
150-00002065	PN16	150	8x22	240				

PN16 – TEAM TEC RAL9017, with spring

Item No.	Connection	DN	nxød	Hcd
M61410	PN16	40	4x18	110

PN10

Item No.	Connection	DN	nxød	Hcd	L	H	ØM	Kg
150-00002066	PN10	200	8x22	295	600	643	400	137
M80078	PN10	250	12x22	350	730	780	400	216

Variants

Meson Group's product offering is larger than displayed here. We have the capability to tailor-make products according to customer needs. Please access a resembling product through www.mesongroup.com and click "Add with note", to request a customized product.

Measures are in mm. Weights are approximate. The information provided may contain errors or omissions, and no rights may be derived from its content. Meson Group reserves the right to update information at any time without prior notice. For the latest revision, always consult www.mesongroup.com. Document created 2026-08-13

