

GLOBE VALVE SDSL STRAIGHT, WITHOUT SPRING, DN80, PN16, GG25/AISI304

Description


Straight type, Cast Iron body, metal seated globe valve with rising stem and bolted bonnet. Raised face flanges.

Standard & Design

Material Body	Cast Iron
Material Sealing Parts	Stainless Steel
Execution	Without Spring
Actuation	Handwheel
Pressure rating	PN16
Connection	PN16
Size	DN80
Standard	DIN
Design code	DIN 86251
Inspection standard	EN 12266
Connection standard	EN 1092
Face to face standard	EN 558, series 1
Min temp Op / peak	0°C
Max temp Op / peak	+180°C
Item number	150-00000816
Item ID	410-2178
Model number	467052

Applications

Fuel oil
Lubricating oil
Flammable hydraulic oil
Cargo oil
Sea water
Water



Measures are in mm. Weights are approximate. The information provided may contain errors or omissions, and no rights may be derived from its content. Meson Group reserves the right to update information at any time without prior notice. For the latest revision, always consult www.mesongroup.com. Document created 2026-08-14



Parts list

No	Part	Material	Code	Comment
1	Body	Cast Iron	GG25	
2	Bonnet	Cast Iron	GG25	
3	Seat	Stainless Steel	1.4301	
4	Disc	Stainless Steel	1.4021	
5	Stem	Stainless Steel	1.4021	
6	Gland packing	Graphite		
7	Gasket	Graphite		
8	Handwheel	Cast Iron	GG25	

Item data

Item number	150-00000816
Pressure rating	PN16
Connection	PN16
DN	80
Hcd	160
nxød	8x18
Inch	3"

Variants

Meson Group's product offering is larger than displayed here. We have the capability to tailor-make products according to customer needs. Please access a resembling product through www.mesongroup.com and click "Add with note", to request a customized product.

Measures are in mm. Weights are approximate. The information provided may contain errors or omissions, and no rights may be derived from its content. Meson Group reserves the right to update information at any time without prior notice. For the latest revision, always consult www.mesongroup.com. Document created 2026-08-14

