

GLOBE VALVE SDSL STRAIGHT, WITHOUT SPRING, GGG40.3/RG5

Description

Straight type, Nodular Cast Iron body, metal seated globe valve with rising stem and bolted bonnet. Raised face flanges.


Standard & Design

Material Body	Ductile Iron
Material Sealing Parts	Copper Alloy
Execution	Without Spring
Actuation	Handwheel
Standard	DIN
Design code	EN 13789
Inspection standard	EN 12266
Connection standard	EN 1092
Face to face standard	EN 558, series 1
Min temp Op / peak	-10°C
Max temp Op / peak	+180°C
Model number	467002;467001;467000



Applications

- Fuel oil
- Lubricating oil
- Flammable hydraulic oil
- Cargo oil
- Non-flammable hydraulic fluid
- Boiler feedwater
- Condensate
- Sea water
- Water



Measures are in mm. Weights are approximate. The information provided may contain errors or omissions, and no rights may be derived from its content. Meson Group reserves the right to update information at any time without prior notice. For the latest revision, always consult www.mesongroup.com. Document created 2026-08-13



Parts list

No	Part	Material	Code	Comment
1	Body	Nodular Cast Iron	GGG40	
2	Bonnet	Nodular Cast Iron	GGG40	
3	Seat	Bronze	RG5	
4	Disc	Bronze	RG5	
5	Stem	Special Brass	Som59	
6	Gland packing	Graphite		
7	Gasket	Graphite		
8	Handwheel	Cast Iron	GG25	

ITEMS

PN16

Item No.	Connection	DN	nxød	Hcd	L	H	ØM	Kg
M61253	PN16	15	4x14	65	130	177	120	3.8
M61293	PN16	20	4x14	75	150	179	120	4.3
M61333	PN16	25	4x14	85	160	198	120	5.4
M61373	PN16	32	4x18	100	180	198	120	7.1
M61413	PN16	40	4x18	110	200	221	140	9.8
M61453	PN16	50	4x18	125	230	224	140	13
M61493	PN16	65	4x18	145	290	267	140	17
M61533	PN16	80	8x18	160	310	292	160	25
M61573	PN16	100	8x18	180	350	325	160	35
M61613	PN16	125	8x18	210	400	370	200	50
M61653	PN16	150	8x22	240	480	420	200	70

PN10

Item No.	Connection	DN	nxød	Hcd
150-00002204	PN10	200	8x22	295

Variants

Meson Group's product offering is larger than displayed here. We have the capability to tailor-make products according to customer needs. Please access a resembling product through www.mesongroup.com and click "Add with note", to request a customized product.

Measures are in mm. Weights are approximate. The information provided may contain errors or omissions, and no rights may be derived from its content. Meson Group reserves the right to update information at any time without prior notice. For the latest revision, always consult www.mesongroup.com. Document created 2026-08-13

