


FLUSHING VALVE, WITHOUT SPRING, LEVER, DN20, PN16, RG5/EPDM

Description

Straight type, Bronze RG5 body, spring loaded, soft sealing self closing flushing valve.
BSPP female threaded ends.

Standard & Design

Material Body	Copper Alloy
Material Sealing Parts	Rubber
Execution	Without Spring
Actuation	Lever
Pressure rating	PN16
Connection	PN16
Size	DN20
Standard	DIN
Inspection standard	EN 12266
Min temp Op / peak	-10°C
Max temp Op / peak	+180°C
Item number	230-00000010
Item ID	466-2740
Model number	314022



Parts list

No	Part	Material	Code	Comment
1	Body	Bronze	CC 491K	
2	Bonnet	Brass	CW 614N	
3	Disc	Brass	CW 614N	
4	Stem	Brass	CW 614N	
5	Disc seal	PTFE		
6	Gasket	Asbestos Free	SIL C4400	
7	Spring	Stainless Steel		
8	Gland packing	Fiber	AF15/MA	
9	Lever	Brass	CW 614N	

Measures are in mm. Weights are approximate. The information provided may contain errors or omissions, and no rights may be derived from its content. Meson Group reserves the right to update information at any time without prior notice. For the latest revision, always consult www.mesongroup.com. Document created 2026-08-14



Item data

Item number	230-00000010
Pressure rating	PN16
Connection	PN16
DN	20
H	142
H1	48
Kg	0.9
L	70
L1	130
Hcd	75
Inch	3/4"

Variants

Meson Group's product offering is larger than displayed here. We have the capability to tailor-make products according to customer needs. Please access a resembling product through www.mesongroup.com and click "Add with note", to request a customized product.

Measures are in mm. Weights are approximate. The information provided may contain errors or omissions, and no rights may be derived from its content. Meson Group reserves the right to update information at any time without prior notice. For the latest revision, always consult www.mesongroup.com. Document created 2026-08-14

