


FLUSHING VALVE, WITHOUT SPRING, LEVER, RG5/EPDM

Description

Straight type, Bronze RG5 body, spring loaded, soft sealing self closing flushing valve.
BSPP female threaded ends.

Standard & Design

Material Body	Copper Alloy
Material Sealing Parts	Rubber
Execution	Without Spring
Actuation	Lever
Standard	DIN
Inspection standard	EN 12266
Min temp Op / peak	-10°C
Max temp Op / peak	+180°C
Model number	314022



Parts list

No	Part	Material	Code	Comment
1	Body	Bronze	CC 491K	
2	Bonnet	Brass	CW 614N	
3	Disc	Brass	CW 614N	
4	Stem	Brass	CW 614N	
5	Disc seal	PTFE		
6	Gasket	Asbestos Free	SIL C4400	
7	Spring	Stainless Steel		
8	Gland packing	Fiber	AF15/MA	
9	Lever	Brass	CW 614N	

Measures are in mm. Weights are approximate. The information provided may contain errors or omissions, and no rights may be derived from its content. Meson Group reserves the right to update information at any time without prior notice. For the latest revision, always consult www.mesongroup.com. Document created 2026-08-13



ITEMS

PN16

Item No.	Connection	DN	L	L1	H	H1	Kg
230-00000009	PN16	15	60	130	111	45	0.8
230-00000010	PN16	20	70	130	142	48	0.9
230-00000011	PN16	25	80	130	84	55	1.6
230-00000012	PN16	32	96	160	131	59	1.6
230-00000013	PN16	40	104	160	133	67	1.9
230-00000014	PN16	50					

Variants

Meson Group's product offering is larger than displayed here. We have the capability to tailor-make products according to customer needs. Please access a resembling product through www.mesongroup.com and click "Add with note", to request a customized product.

Measures are in mm. Weights are approximate. The information provided may contain errors or omissions, and no rights may be derived from its content. Meson Group reserves the right to update information at any time without prior notice. For the latest revision, always consult www.mesongroup.com. Document created 2026-08-13

