

FIRE VALVE STRAIGHT, WITHOUT SPRING, WITH STORZ 52-C COUPLING, DN65, PN16, RG5/NBR

Description

Bronze RG5 body soft sealing fire valve. Rising stem with bolted bonnet. Straight hose connection. Raised face flanged inlet, BSP male threaded outlet.

Standard & Design

Material Body	Copper Alloy
Material Sealing Parts	Rubber
Execution	Without Spring
Actuation	Handwheel
Item characteristics	With Storz 52-C Coupling
Pressure rating	PN16
Connection	PN16
Size	DN65
Standard	DIN
Face to face standard	DIN 86211
Item number	90-00000112
Item ID	470-2748
Model number	356622

Parts list

No	Part	Material	Code	Comment
1	Body	Bronze	CC491K	

Item data

Item number	90-00000112
Pressure rating	PN16
Connection	PN16
Item characteristics	With Storz 52-C Coupling
DN	65
Hcd	145
Inch	2 1/2"

Variants

Meson Group's product offering is larger than displayed here. We have the capability to tailor-make products according to customer needs. Please access a resembling product through www.mesongroup.com and click "Add with note", to request a customized product.

Measures are in mm. Weights are approximate. The information provided may contain errors or omissions, and no rights may be derived from its content. Meson Group reserves the right to update information at any time without prior notice. For the latest revision, always consult www.mesongroup.com. Document created 2026-08-13

