


FIRE VALVE ANGLE, WITHOUT SPRING, DN65, PN16, RG5/NBR

Description

Bronze RG5 body soft sealing fire valve. Rising stem with bolted bonnet. Angled hose connection. Raised face flanged inlet, BSP male threaded outlet.

Standard & Design

Material Body	Copper Alloy
Material Sealing Parts	Rubber
Execution	Without Spring
Actuation	Handwheel
Pressure rating	PN16
Connection	PN16
Size	DN65
Standard	DIN
Face to face standard	DIN 86211
Item number	90-00000040
Item ID	471-2760
Model number	356722



Parts list

No	Part	Material	Code	Comment
1	Body	Bronze	CC491K	

Measures are in mm. Weights are approximate. The information provided may contain errors or omissions, and no rights may be derived from its content. Meson Group reserves the right to update information at any time without prior notice. For the latest revision, always consult www.mesongroup.com. Document created 2026-08-14



Item data

Item number	90-00000040
Pressure rating	PN16
Connection	PN16
DN	65
G	2 1/2"
H	180
Hcd	145
Kg	10.2
L	95
L1	90
nxød	4x18
ØM	160
Inch	2 1/2"

Variants

Meson Group's product offering is larger than displayed here. We have the capability to tailor-make products according to customer needs. Please access a resembling product through www.mesongroup.com and click "Add with note", to request a customized product.

Measures are in mm. Weights are approximate. The information provided may contain errors or omissions, and no rights may be derived from its content. Meson Group reserves the right to update information at any time without prior notice. For the latest revision, always consult www.mesongroup.com. Document created 2026-08-14

