


FIRE VALVE ANGLE 30DEG, WITHOUT SPRING, DN50, PN16, RG7/NBR

Description

Bronze RG5 body soft sealing fire valve. Rising stem with screwed and secured bonnet. Angled (30° from flange) hose connection. Flat face flanged inlet, BSP male threaded outlet.

Standard & Design

Material Body	Copper Alloy
Material Sealing Parts	Rubber
Execution	Without Spring
Actuation	Handwheel
Pressure rating	PN16
Connection	ANSI150
Size	DN50
Standard	Hybrid
Item number	90-00000006
Item ID	472-2774
Model number	355922



Parts list

No	Part	Material	Code	Comment
1	Body	Bronze	CC493K	

Measures are in mm. Weights are approximate. The information provided may contain errors or omissions, and no rights may be derived from its content. Meson Group reserves the right to update information at any time without prior notice. For the latest revision, always consult www.mesongroup.com. Document created 2026-08-13



Item data

Item number	90-00000006
Pressure rating	PN16
Connection	ANSI150
DN	50
G	2"
H	195
Hcd	125
Kg	4.4
L	100
nxød	4x18
ØM	100
Inch	2"

Variants

Meson Group's product offering is larger than displayed here. We have the capability to tailor-make products according to customer needs. Please access a resembling product through www.mesongroup.com and click "Add with note", to request a customized product.

Measures are in mm. Weights are approximate. The information provided may contain errors or omissions, and no rights may be derived from its content. Meson Group reserves the right to update information at any time without prior notice. For the latest revision, always consult www.mesongroup.com. Document created 2026-08-13

