

BALL VALVE 2-PCE FLANGED, NON-DIRECT, LEVER, DN150, PN16, AISI316/AISI316/PTFE

Description

Two piece, full bore, Stainless Steel body ball valve with Stainless Steel ball and PTFE seat. Raised face flanges.


Standard & Design

Material Body	Stainless Steel
Material Ball	Stainless Steel
Material Seat	Polymer Based
Execution	Non-Direct
Actuation	Lever
Pressure rating	PN16
Connection	PN16
Size	DN150
Standard	DIN
Design code	ASME B16.34
Inspection standard	EN 12266
Face to face standard	EN 558, series 14
Item number	20-00000402
Item ID	500-3302
Model number	445194



Applications

Corrosive fluids
 Fuel oil
 Lubricating oil
 Flammable hydraulic oil
 Cargo oil
 Non-flammable hydraulic fluid
 Boiler feedwater
 Condensate
 Sea water
 Water



Measures are in mm. Weights are approximate. The information provided may contain errors or omissions, and no rights may be derived from its content. Meson Group reserves the right to update information at any time without prior notice. For the latest revision, always consult www.mesongroup.com. Document created 2026-08-14



Parts list

No	Part	Material	Code	Comment
1	Body	Stainless Steel	1.4408	
2	Cap	Stainless Steel	1.4408	
3	Ball	Stainless Steel	1.4408	
4	Seat	PTFE		
5	Stem	Stainless Steel	SUS316	
6	Handle	Stainless Steel, Plastic Cover	SUS304	

Item data

Item number	20-00000402
Pressure rating	PN16
Connection	PN16
DN	150
H	247
Hcd	240
Kg	53
L	350
L1	750
nxød	8x22
Inch	6"

Variants

Meson Group's product offering is larger than displayed here. We have the capability to tailor-make products according to customer needs. Please access a resembling product through www.mesongroup.com and click "Add with note", to request a customized product.

Measures are in mm. Weights are approximate. The information provided may contain errors or omissions, and no rights may be derived from its content. Meson Group reserves the right to update information at any time without prior notice. For the latest revision, always consult www.mesongroup.com. Document created 2026-08-14

