



BALL VALVE 3-WAY ALL FEMALE L-PORT, NON-DIRECT, LEVER, DN15, PN63, AISI316/AISI316/PTFE

Description

3-way, reduced bore, Stainless Steel body ball valve with Stainless Steel ball and PTFE seat. Female threaded ends.

Standard & Design

Material Body	Stainless Steel
Material Ball	Stainless Steel
Material Seat	Polymer Based
Execution	Non-Direct
Actuation	Lever
Pressure rating	PN63
Size	DN15
Standard	DIN
Item number	20-00000943
Item ID	527-3454
Model number	448095



Parts list

No	Part	Material	Code	Comment
1	Body	Stainless Steel	ASTM A351-CF8M	
2	Cap	Stainless Steel	ASTM A351-CF8M	
3	Ball	Stainless Steel	ASTM A351-CF8M	
4	Seat	PTFE		
5	Stem	Stainless Steel	AISI 316	
6	Handle	Stainless Steel, Plastic Cover	AISI 304	

Measures are in mm. Weights are approximate. The information provided may contain errors or omissions, and no rights may be derived from its content. Meson Group reserves the right to update information at any time without prior notice. For the latest revision, always consult www.mesongroup.com. Document created 2026-08-14



Item data

Item number	20-00000943
Pressure rating	PN63
B	36
DN	15
H	65
Kg	0.9
L	75
L1	132
ØA	12.7
Inch	1/2"

Variants

Meson Group’s product offering is larger than displayed here. We have the capability to tailor-make products according to customer needs. Please access a resembling product through www.mesongroup.com and click “Add with note”, to request a customized product.

Measures are in mm. Weights are approximate. The information provided may contain errors or omissions, and no rights may be derived from its content. Meson Group reserves the right to update information at any time without prior notice. For the latest revision, always consult www.mesongroup.com. Document created 2026-08-14

