

GATE VALVE NON-RISING INDICATOR FLANGED SOSE, With Indicator, DN500, PN6, GGG40.3/NBR

Description

Nodular Cast Iron body gate valve, NBR coated wedge. Non rising stem with open/close indicator and bolted bonnet. Standardized top flange for actuator mounting. Raised face flanges.

Standard & Design

Material Body	Ductile Iron
Material Sealing Parts	Rubber
Execution	With Indicator
Actuation	Handwheel
Pressure rating	PN6
Connection	PN10
Size	DN500
Standard	DIN
Design code	EN 1171
Inspection standard	EN 12266
Face to face standard	EN 558, series 14
Min temp Op / peak	-10°C
Max temp Op / peak	+80°C
Item number	M50000
Item number prod	GT05000000
Item ID	614-2865
Model number	620700

Parts list

No	Part	Material	Code	Comment
1	Body	Nodular Cast Iron	GGG40.3	

Item data

Item number	M50000
Pressure rating	PN6
Connection	PN10
B	720
DN	500
H	1250
Hcd	620
Kg	360
L	350
nxød	20x26
ØM	560
Inch	20"

Measures are in mm. Weights are approximate. The information provided may contain errors or omissions, and no rights may be derived from its content. Meson Group reserves the right to update information at any time without prior notice. For the latest revision, always consult www.mesongroup.com. Document created 2026-08-13



Variants

Meson Group's product offering is larger than displayed here. We have the capability to tailor-make products according to customer needs. Please access a resembling product through www.mesongroup.com and click "Add with note", to request a customized product.

Measures are in mm. Weights are approximate. The information provided may contain errors or omissions, and no rights may be derived from its content. Meson Group reserves the right to update information at any time without prior notice. For the latest revision, always consult www.mesongroup.com. Document created 2026-08-13

