



BUTTERFLY VALVE VULCANIZED LINER WAFER, LEVER, GGG40.3/AISI316/NBR

Description

Nodular Cast Iron body, vulcanized liner wafer type butterfly valve with Stainless Steel disc. Centric free stem with standardized pattern for actuator mounting. Can handle negative pressure (vacuum), due to the meticulous vulcanization process.

Standard & Design

Material Body	Ductile Iron
Material Disc	Stainless Steel
Material Liner	NBR
Actuation	Lever
Standard	DIN
Face to face standard	EN 558, series 20
Min temp Op / peak	-15°C / -25°C
Max temp Op / peak	+80°C / +95°C
Model number	700903;700902



Parts list

No	Part	Material	Code	Comment
1	Body	Nodular Cast Iron	GGG40.3	
2	Disc	Stainless Steel	AISI316	
3	Seat	NBR	NBR	
4	Stem	Stainless Steel	AISI431	
5	Pin	Duplex	1.4462	

Measures are in mm. Weights are approximate. The information provided may contain errors or omissions, and no rights may be derived from its content. Meson Group reserves the right to update information at any time without prior notice. For the latest revision, always consult www.mesongroup.com. Document created 2026-08-14



ITEMS

PN16

Item No.	Connection	DN	ØD2	L	L1	L2	H	H1	H2	Kg
M34311	PN6/PN10/PN16/PN25/ANSI150/JIS5K/JIS10K	40	90	33	232	101	233.5	67	113	2.2
M34312	PN6/PN10/PN16/PN25/ANSI150/JIS5K/JIS10K	50	90	43	232	101	242.5	71	118	3.1
M34313	PN6/PN10/PN16/PN25/ANSI150/JIS5K/JIS10K	65	90	46	232	101	265.5	86	126	3.8
M34314	PN6/PN10/PN16/PN25/ANSI150/JIS5K/JIS10K	80	90	46	232	101	274.5	88	133	4.3
M34315	PN6/PN10/PN16/PN25/ANSI150/JIS5K/JIS10K	100	90	52	232	101	306.5	106	147	4.8
M34316	PN6/PN10/PN16/PN25/ANSI150/JIS5K/JIS10K	125	90	56	329	101	342	118	160	8.5
M34317	PN6/PN10/PN16/PN25/ANSI150/JIS5K/JIS10K	150	90	56	329	101	384	140	180	10.3
40-00002867	PN6/PN10/PN16/PN25/ANSI150/JIS5K/JIS10K	200	90	60	218	53		167	204	15.5

Variants

For wafer type valves above DN400, semilug type is offered. Meson Group's product offering is larger than displayed here. We have the capability to tailor-make products according to customer needs. Please access a resembling product through www.mesongroup.com and click "Add with note", to request a customized product.

Measures are in mm. Weights are approximate. The information provided may contain errors or omissions, and no rights may be derived from its content. Meson Group reserves the right to update information at any time without prior notice. For the latest revision, always consult www.mesongroup.com. Document created 2026-08-14

