



BUTTERFLY VALVE VULCANIZED LINER WAFER, BARE STEM, GGG40.3/AISI316/FKM

Description

Nodular Cast Iron body, vulcanized liner wafer type butterfly valve with Stainless Steel disc. Centric free stem with standardized pattern for actuator mounting. Can handle negative pressure (vacuum), due to the meticulous vulcanization process.

Standard & Design

Material Body	Ductile Iron
Material Disc	Stainless Steel
Material Liner	FKM
Actuation	Bare Stem Parallel
Standard	DIN
Face to face standard	EN 558, series 20
Min temp Op / peak	-10°C / -20°C
Max temp Op / peak	+160°C / +180°C
Model number	702903;702902;702901



Parts list

No	Part	Material	Code	Comment
1	Body	Nodular Cast Iron	GGG40.3	
2	Disc	Stainless Steel	AISI316	
3	Seat	FKM	FKM	
4	Stem	Stainless Steel	AISI431	
5	Pin	Duplex	1.4462	

Measures are in mm. Weights are approximate. The information provided may contain errors or omissions, and no rights may be derived from its content. Meson Group reserves the right to update information at any time without prior notice. For the latest revision, always consult www.mesongroup.com. Document created 2026-08-13



ITEMS

PN16

Item No.	Connection	DN	ØD2	L	H1	H2	H3	S	Kg
M34334	PN6/PN10/PN16/PN25/ANSI150/JIS5K/JIS10K	40	90	33	67	113	19	11	1.5
M34335	PN6/PN10/PN16/PN25/ANSI150/JIS5K/JIS10K	50	90	43	71	118	19	11	2.4
M34336	PN6/PN10/PN16/PN25/ANSI150/JIS5K/JIS10K	65	90	46	86	126	19	11	3.1
M34337	PN6/PN10/PN16/PN25/ANSI150/JIS5K/JIS10K	80	90	46	88	133	19	11	3.6
M34338	PN6/PN10/PN16/PN25/ANSI150/JIS5K/JIS10K	100	90	52	106	147	19	11	4.8
M34339	PN6/PN10/PN16/PN25/ANSI150/JIS5K/JIS10K	125	90	56	118	160	19	14	7.2
M34340	PN6/PN10/PN16/PN25/ANSI150/JIS5K/JIS10K	150	90	56	140	180	19	14	9
M34341	PN6/PN10/PN16/PN25/ANSI150/JIS5K/JIS10K	200	90	60	167	204	25	17	14
M34342	PN6/PN10/PN16/PN25/ANSI150/JIS5K/JIS10K	250	125	68	202	245	30	22	22
M34343	PN6/PN10/PN16/PN25/ANSI150/JIS5K/JIS10K	300	125	78	240	270	30	22	33
M34236	PN6/PN10/PN16/PN25/ANSI150/JIS5K/JIS10K	400	150	102	305	350	30	27	70

PN10

Item No.	Connection	DN	ØD2	L	H1	H2	H3	S	Kg
M34235	PN6/PN10/PN16/PN25/ANSI150/JIS5K/JIS10K	350	150	78	288	315	30	27	43

Variants

For wafer type valves above DN400, semilug type is offered. Meson Group's product offering is larger than displayed here. We have the capability to tailor-make products according to customer needs. Please access a resembling product through www.mesongroup.com and click "Add with note", to request a customized product.

Measures are in mm. Weights are approximate. The information provided may contain errors or omissions, and no rights may be derived from its content. Meson Group reserves the right to update information at any time without prior notice. For the latest revision, always consult www.mesongroup.com. Document created 2026-08-13

