





BUTTERFLY VALVE VULCANIZED LINER LUG, GEARBOX, DN700, PN10, GGG40.3/AISI316/EPDM

Description

Nodular Cast Iron body, vulcanized liner lugged type butterfly valve with Stainless Steel disc. Centric free stem with standardized pattern for actuator mounting. Can handle negative pressure (vacuum), due to the meticulous vulcanization process.

Standard & Design

Material Body	Ductile Iron
Material Disc	Stainless Steel
Material Liner	EPDM
Actuation	Gearbox
Pressure rating	PN10
Connection	PN10
Size	DN700
Standard	DIN
Face to face standard	EN 558, series 20
Min temp Op / peak	-25°C / -35°C
Max temp Op / peak	+100°C / +125°C
Item number	M34214
Item ID	701-0366
Model number	711901



Parts list

No	Part	Material	Code	Comment
1	Body	Nodular Cast Iron	GGG40.3	
2	Disc	Stainless Steel	AISI316	
3	Seat	EPDM	EPDM	
4	Stem	Stainless Steel	AISI431	
5	Pin	Duplex	1.4462	

Measures are in mm. Weights are approximate. The information provided may contain errors or omissions, and no rights may be derived from its content. Meson Group reserves the right to update information at any time without prior notice. For the latest revision, always consult www.mesongroup.com. Document created 2026-08-14



Item data

Item number	M34214
Pressure rating	PN10
Connection	PN10
DN	700
H1	485
H2	555
Hcd	840
Kg	321
L	165
L1	344
L2	53
nxød	24xM27
ØM	500
Inch	28"
ISO5211	F16

Variants

Meson Group's product offering is larger than displayed here. We have the capability to tailor-make products according to customer needs. Please access a resembling product through www.mesongroup.com and click "Add with note", to request a customized product.

Measures are in mm. Weights are approximate. The information provided may contain errors or omissions, and no rights may be derived from its content. Meson Group reserves the right to update information at any time without prior notice. For the latest revision, always consult www.mesongroup.com. Document created 2026-08-14

