



BUTTERFLY VALVE VULCANIZED LINER LUG, LEVER, DN150, PN16, GGG40.3/1.4469/EPDM

Description

Nodular Cast Iron body, vulcanized liner wafer type butterfly valve with Super Duplex disc. Centric free stem with standardized pattern for actuator mounting. Can handle negative pressure (vacuum), due to the meticulous vulcanization process.

Standard & Design

Material Body	Ductile Iron
Material Disc	Stainless Steel
Material Liner	EPDM
Actuation	Lever
Pressure rating	PN16
Connection	PN16
Size	DN150
Standard	DIN
Face to face standard	EN 558, series 20
Min temp Op / peak	-25°C / -35°C
Max temp Op / peak	+100°C / +125°C
Item number	M95477
Item number prod	BF09547700
Item ID	701-0469
Model number	711802



Parts list

No	Part	Material	Code	Comment
1	Body	Nodular Cast Iron	GGG40.3	
2	Disc	Duplex	1.4469	
3	Seat	EPDM	EPDM	
4	Stem	Stainless Steel	AISI431	
5	Pin	Duplex	1.4462	

Measures are in mm. Weights are approximate. The information provided may contain errors or omissions, and no rights may be derived from its content. Meson Group reserves the right to update information at any time without prior notice. For the latest revision, always consult www.mesongroup.com. Document created 2026-08-14



Item data

Item number	M95477
Pressure rating	PN16
Connection	PN16
DN	150
H	384
H1	140
H2	180
Hcd	240
Kg	14
L	56
L1	329
L2	101
nxød	8xM20
Inch	6"
ISO5211	F07

Variants

Meson Group's product offering is larger than displayed here. We have the capability to tailor-make products according to customer needs. Please access a resembling product through www.mesongroup.com and click "Add with note", to request a customized product.

Measures are in mm. Weights are approximate. The information provided may contain errors or omissions, and no rights may be derived from its content. Meson Group reserves the right to update information at any time without prior notice. For the latest revision, always consult www.mesongroup.com. Document created 2026-08-14

