






BUTTERFLY VALVE VULCANIZED LINER LUG, BARE STEM, DN600, PN10, GGG40.3/C958/EPDM

Description

Nodular Cast Iron body, vulcanized liner lugged type butterfly valve with Stainless Steel disc. Centric free stem with standardized pattern for actuator mounting. Can handle negative pressure (vacuum), due to the meticulous vulcanization process.

Standard & Design

|                       |                    |
|-----------------------|--------------------|
| Material Body         | Ductile Iron       |
| Material Disc         | Copper Alloy       |
| Material Liner        | EPDM               |
| Actuation             | Bare Stem Parallel |
| Pressure rating       | PN10               |
| Connection            | PN10               |
| Size                  | DN600              |
| Standard              | DIN                |
| Design code           | API 609            |
| Inspection standard   | API 598            |
| Face to face standard | EN 558, series 20  |
| Min temp Op / peak    | -25°C / -35°C      |
| Max temp Op / peak    | +100°C / +125°C    |
| Item number           | M33544             |
| Item number prod      | BF03354400         |
| Item ID               | 701-0577           |
| Model number          | 711701             |



Parts list

| No | Part    | Material          | Code    | Comment |
|----|---------|-------------------|---------|---------|
| 1  | Body    | Nodular Cast Iron | GGG40.3 |         |
| 2  | Disc    | Aluminium Bronze  | CC333G  |         |
| 3  | Seat    | EPDM              | EPDM    |         |
| 4  | Stem    | Stainless Steel   | AISI431 |         |
| 5  | Pin     | Duplex            | 1.4462  |         |
| 6  | Bearing | Copper Alloy      | CC491K  |         |
| 7  | Bushing | Plastic           | PTFE    |         |

Measures are in mm. Weights are approximate. The information provided may contain errors or omissions, and no rights may be derived from its content. Meson Group reserves the right to update information at any time without prior notice. For the latest revision, always consult [www.mesongroup.com](http://www.mesongroup.com). Document created 2026-08-13

**Item data**

|                 |        |
|-----------------|--------|
| Item number     | M33544 |
| Pressure rating | PN10   |
| Connection      | PN10   |
| DN              | 600    |
| H1              | 431    |
| H2              | 465    |
| H3              | 48     |
| Hcd             | 725    |
| Kg              | 211    |
| L               | 154    |
| nxød            | 20xM27 |
| S               | 46     |
| ØD2             | 210    |
| Inch            | 24"    |
| ISO5211         | F16    |

**Variants**

Meson Group's product offering is larger than displayed here. We have the capability to tailor-make products according to customer needs. Please access a resembling product through [www.mesongroup.com](http://www.mesongroup.com) and click "Add with note", to request a customized product.

Measures are in mm. Weights are approximate. The information provided may contain errors or omissions, and no rights may be derived from its content. Meson Group reserves the right to update information at any time without prior notice. For the latest revision, always consult [www.mesongroup.com](http://www.mesongroup.com). Document created 2026-08-13

