



BUTTERFLY VALVE VULCANIZED LINER DOUBLE FLANGED, BARE STEM, DN600, PN10, GGG40.3/1.4469/EPDM

Description

Nodular Cast Iron body, vulcanized liner double flange type butterfly valve with Super Duplex disc. Centric free stem with standardized pattern for actuator mounting. Can handle negative pressure (vacuum), due to the meticulous vulcanization process.

Standard & Design

Material Body	Ductile Iron
Material Disc	Stainless Steel
Material Liner	EPDM
Actuation	Bare Stem Parallel
Pressure rating	PN10
Connection	PN10
Size	DN600
Standard	DIN
Face to face standard	EN 558, series 13
Min temp Op / peak	-25°C / -35°C
Max temp Op / peak	+100°C / +125°C
Item number	40-00002707
Item ID	703-1167
Model number	731801



Parts list

No	Part	Material	Code	Comment
1	Body	Nodular Cast Iron	GGG40.3	
2	Disc	Duplex	1.4469	
3	Seat	EPDM	EPDM	
4	Stem	Stainless Steel	AISI431	
5	Pin	Duplex	1.4462	

Measures are in mm. Weights are approximate. The information provided may contain errors or omissions, and no rights may be derived from its content. Meson Group reserves the right to update information at any time without prior notice. For the latest revision, always consult www.mesongroup.com. Document created 2026-08-13



Item data

Item number	40-00002707
Pressure rating	PN10
Connection	PN10
DN	600
H1	431
H2	465
H3	48
Hcd	725
L	267
nxød	20x26
S	46
Inch	24"
ISO5211	F16

Variants

Meson Group’s product offering is larger than displayed here. We have the capability to tailor-make products according to customer needs. Please access a resembling product through www.mesongroup.com and click “Add with note”, to request a customized product.

Measures are in mm. Weights are approximate. The information provided may contain errors or omissions, and no rights may be derived from its content. Meson Group reserves the right to update information at any time without prior notice. For the latest revision, always consult www.mesongroup.com. Document created 2026-08-13

