



BUTTERFLY VALVE VULCANIZED LINER SEMI LUG, GEARBOX, GGG40.3/C958/NBR

Description

Nodular Cast Iron body, vulcanized liner wafer type butterfly valve with Aluminium Bronze disc. Centric free stem with standardized pattern for actuator mounting. Can handle negative pressure (vacuum), due to the meticulous vulcanization process.

Standard & Design

Material Body	Ductile Iron
Material Disc	Copper Alloy
Material Liner	NBR
Actuation	Gearbox
Standard	DIN
Face to face standard	EN 558, series 20
Min temp Op / peak	-15°C / -25°C
Max temp Op / peak	+80°C / +95°C
Model number	700701



Parts list

No	Part	Material	Code	Comment
1	Body	Nodular Cast Iron	GGG40.3	
2	Disc	Aluminium Bronze	CC333G	
3	Seat	NBR	NBR	
4	Stem	Stainless Steel	AISI431	
5	Pin	Duplex	1.4462	

ITEMS

PN10

Item No.	Connection	DN	Hcd	ØD2	L	L1	L2	H	H1	H2	ØM	Kg
M34410	PN10	450	565	175	114	287	101	810	335	375	400	131
M34411	PN10	500	620	175	127	357	123	885	379	415	500	170

Measures are in mm. Weights are approximate. The information provided may contain errors or omissions, and no rights may be derived from its content. Meson Group reserves the right to update information at any time without prior notice. For the latest revision, always consult www.mesongroup.com. Document created 2026-08-13



Variants

For wafer type valves above DN400, semilug type is offered. Meson Group's product offering is larger than displayed here. We have the capability to tailor-make products according to customer needs. Please access a resembling product through www.mesongroup.com and click "Add with note", to request a customized product.

Measures are in mm. Weights are approximate. The information provided may contain errors or omissions, and no rights may be derived from its content. Meson Group reserves the right to update information at any time without prior notice. For the latest revision, always consult www.mesongroup.com. Document created 2026-08-13

