

BUTTERFLY VALVE DOUBLE EXCENTRIC WAFER, GEARBOX, DN65, PN16, AISI316/AISI316/PTFE

Description

High performance, double offset, wafer type butterfly valve. Sealing in PTFE.
Standardized pattern for actuator mounting. Blow-out proof shaft.

Standard & Design

Material Body	Stainless Steel
Material Disc	Stainless Steel
Material Liner	Polymer Based
Actuation	Gearbox
Pressure rating	PN16
Connection	PN16
Size	DN65
Standard	DIN
Face to face standard	JIS B2002
Item number	40-00000571
Item ID	720-1743
Model number	762992

Parts list

No	Part	Material	Code	Comment
1	Body	Stainless Steel	CF8M	
2	Disc	Stainless Steel	AISI316	
3	Seat	Polymer	PTFE	
4	Stem	Stainless Steel	316L	
5	Pin	Stainless Steel	316L	
6	Packing	Polymer	PTFE	
7	Gearbox	Cast Iron	GG25	

Measures are in mm. Weights are approximate. The information provided may contain errors or omissions, and no rights may be derived from its content. Meson Group reserves the right to update information at any time without prior notice. For the latest revision, always consult www.mesongroup.com. Document created 2026-08-14



Item data

Item number	40-00000571
Pressure rating	PN16
Connection	PN16
DN	65
H	290
H1	76
H2	150
Hcd	145
Kg	6.4
L	46
L1	155
ØM	160
H3	41
Inch	2 1/2"
ISO5211	F05/F07
nxød	2x18

Variants

Meson Group's product offering is larger than displayed here. We have the capability to tailor-make products according to customer needs. Please access a resembling product through www.mesongroup.com and click "Add with note", to request a customized product.

Measures are in mm. Weights are approximate. The information provided may contain errors or omissions, and no rights may be derived from its content. Meson Group reserves the right to update information at any time without prior notice. For the latest revision, always consult www.mesongroup.com. Document created 2026-08-14

