

BUTTERFLY VALVE DOUBLE EXCENTRIC LUG, GEARBOX, AISI316/AISI316/PTFE

Description

High performance, double offset, wafer type butterfly valve. Sealing in PTFE.
Standardized pattern for actuator mounting. Blow-out proof shaft.

Standard & Design

Material Body	Stainless Steel
Material Disc	Stainless Steel
Material Liner	Polymer Based
Actuation	Gearbox
Standard	DIN
Face to face standard	EN 558, series 20
Model number	762992

Parts list

No	Part	Material	Code	Comment
1	Body	Stainless Steel	CF8M	
2	Disc	Stainless Steel	AISI316	
3	Seat	Polymer	PTFE	
4	Stem	Stainless Steel	316L	
5	Pin	Stainless Steel	316L	
6	Packing	Polymer	PTFE	
7	Gearbox	Cast Iron	GG25	

ITEMS

PN16

Item No.	Connection	DN	nxød	Hcd	L	L1	H	H1	H2	ØM	Kg
40-00001957	PN16	50	4xM16	125	43	155	276.5	70	142.5	160	7.5
40-00001958	PN16	65	4xM16	145	46	155	290	76	150	160	9.3
40-00001959	PN16	80	8xM16	160	46	155	331.5	99	168.5	160	11.1
40-00001960	PN16	100	8xM16	180	52	155	354	110	180	160	13.1
40-00001961	PN16	150	8xM20	240	56	155	399	140	195	160	19.5
40-00001962	PN16	200	12xM20	295	60	220	490.7	176	240	200	32.3
40-00001963	PN16	250	12xM24	355	70	220	591.7	215	302	200	47.3

Variants

Meson Group's product offering is larger than displayed here. We have the capability to tailor-make products according to customer needs. Please access a resembling product through www.mesongroup.com and click "Add with note", to request a customized product.

Measures are in mm. Weights are approximate. The information provided may contain errors or omissions, and no rights may be derived from its content. Meson Group reserves the right to update information at any time without prior notice. For the latest revision, always consult www.mesongroup.com. Document created 2026-08-14

