



Marine & Offshore

Certificate number: 69693/A0 BV

File number: .

Product code: 2203I

This certificate is not valid when presented without the full attached schedule composed of 7 sections

www.veristar.com

TYPE APPROVAL CERTIFICATE

This certificate is issued to

Meson (Changzhou) Flow Control System Co., Ltd.
Changzhou - CHINA

for the type of product

GATE VALVES

Gate valve flanged ends with metal seated and soft seat

Requirements:

Bureau Veritas Rules for the Classification of Steel Ships

This certificate is issued to attest that Bureau Veritas Marine & Offshore did undertake the relevant approval procedures for the product identified above which was found to comply with the relevant requirements mentioned above.

This certificate will expire on: 20 Jan 2027

For Bureau Veritas Marine & Offshore,

At BV SHANGHAI, on 20 Jan 2022,

Jennifer Zhang



This certificate remains valid until the date stated above, unless cancelled or revoked, provided the conditions indicated in the subsequent page(s) are complied with and the product remains satisfactory in service. This certificate will not be valid if the applicant makes any changes or modifications to the approved product, which have not been notified to, and agreed in writing with Bureau Veritas Marine & Offshore. Should the specified regulations or standards be amended during the validity of this certificate, the product(s) is/are to be re-approved prior to it/they being placed on board vessels to which the amended regulations or standards apply. This certificate is issued within the scope of the General Conditions of Bureau Veritas Marine & Offshore available on the internet site www.veristar.com. Any Person not a party to the contract pursuant to which this document is delivered may not assert a claim against Bureau Veritas Marine & Offshore for any liability arising out of errors or omissions which may be contained in said document, or for errors of judgement, fault or negligence committed by personnel of the Society or of its Agents in establishment or issuance of this document, and in connection with any activities for which it may provide.

The electronic version is available at: <http://www.veristarm.com/veristarnb/jsp/viewPublicPdfTypepec.jsp?id=9qgcdzmkge>

BV Mod. Ad.E 530 June 2017

This certificate consists of 4 page(s)

THE SCHEDULE OF APPROVAL

1. PRODUCT DESCRIPTION :

Gate valve flanged ends with metal seat and soft seat

1.1 Ratings

Model	Gate valve
Size range (mm)	DN 40 to DN 600
Design standard	EN 558
Class range	PN 16: DN 40 ~ DN 150 PN 10: DN 200 ~ DN 300 PN 6: DN 350 ~ DN 500 PN 4: DN 600
Design pressure	16 bar : DN 40 ~ DN 150 10 bar : DN 200 ~ DN 300 6 bar : DN 350 ~ DN 500 4 bar : DN 600
Design temperature	Metal seat : -10° to +120° Soft seat : NBR: -35°C to 95°C EPDM: -40°C to 110°C
End connections	Flange
Design specification	Gate valve : metal seat / soft seat

1.2 Material

Part	Material	Material
	Metal seat	Soft seat
Body	GGG40, GGG40.3, WCB, WC, CF8M, CF3M, C954, C958, RG5	GGG40/GGG40.3/WCB/WCC/C954/C958
Bonnet	GGG40, GGG40.3, WCB, WC, CF8M, CF3M, C954, C958, RG5	GGG40/GGG40.3/WCB/WCC/C954/C958
Stem	Brass	AISI316L
Seat	Bronze	N/A
Disc	GGG40, GGG40.3, WCB, WC, CF8M, CF3M, C954, C958, RG5	GGG40/GGG40.3 / NBR/EPDM
Gasket	Graphite	NBR/EPDM
Wedge	GGG40/GGG40.3/WCB/WCC/C954/C958/CF8M/CF3M/RG5	Core : GGG40/GGG40.3 Coating : NBR/EPDM

2. DOCUMENTS AND DRAWINGS :

- Drawing N° DDWG-GATE-MESE Rev.A dated 16/11/2021: gate valve metal seat
- Drawing N° DDWG-GATE-SOSE Rev. B dated 12/11/2021: gate valve soft seat
- Manual of installation, use and maintenance for soft seat N°IOM-001 Rev. 3
- Manual of installation, use and maintenance for metal seat N°IOM-006 Rev. 1
- Material datasheet N°Technical Specification Rev.1 dated 14/12/2021

No departure from the above documents shall be made without the prior consent of the Society. The manufacturer must inform the Society of any modification or changes to these documents and drawings.

3. TEST REPORTS :

Not required

Fire resistance test not performed

4. APPLICATION / LIMITATION :

4.1 - May be used for the following services on board: - Sea water and fresh water - Cargo oil for tankers - Fuel-oil and lubricating oil transfer - Hydraulic oil

4.2 - The valves belong to Class I, Class II and Class III according to the relevant requirements stated in Part C, Ch 1, Sec 10. Valves fitted on the ship side and collision bulkhead, and valves fitted on fuel oil and lub oil tanks under static pressure belong to Class II.

4.3 - The valve body, disc and seat should be suitable for the intended service. In particular the nature of materials, joints included, is to be selected according to the fluid to be conveyed and the temperature.

4.4 - The approval does not include any operating gear for remote control of the valves.

4.5 - Bilge valves will be fitted in association with a non-return valve.

4.6 - The valves are to be installed according to the manufacturer's instructions and Society's Rule requirements.

4.7 - The use of stainless steel and grey cast iron is to be restricted as per the BUREAU VERITAS Rules.

5. PRODUCTION SURVEY REQUIREMENTS :

5.1 - The products are to be supplied by **Meson (Changzhou) Flow Control System Co., Ltd** in compliance with the type and the requirements described in this certificate.

5.2 - This type of product is within the category IBV of BV Rule Note NR320.

5.3 - BV product certificate is required.

5.4 - BV Certificate is required for materials of valve housings of class I (DN≥50) or class II (DN≥100). Materials of valve housings of class I (DN<50) or class II (DN<100) and for other parts are to be with Work's certificates.

5.5 - Each valve housing for class I and class II is to be hydraulically pressure tested to 1,5 times the design pressure. Valves intended to be fitted on the shipside below the load waterline are to be tested by hydraulic pressure not less than 0,5 MPa.

5.6 - For information, Meson (Changzhou) Flow Control System Co., Ltd has declared to Bureau Veritas the following production sites:

Meson (Changzhou) Flow Control System Co., Ltd
Building No 16, Xin Yu Logistics Park ,
Renmin Road No 8, YaoGuan, Wujin
Changzhou, Jiangsu Province
Peoples Republic of China

Meson AB
Kullsgårdsvägen 27
312 34 Laholm
SWEDEN

6. MARKING OF PRODUCT :

Each valve shall be permanently marked with at least:

- Manufacturer's name or logo
- Type designation
- Maximum working Pressure
- Society's brand as relevant

7. OTHERS :

It is **Meson (Changzhou) Flow Control System Co., Ltd**'s responsibility to inform shipbuilders or their sub-contractors of the proper methods of fitting, use and general maintenance of the approved equipment and the conditions of this approval.

*** END OF CERTIFICATE ***